

SAFETY DATA SHEET

Version: 1.1
Revision Date: 7/30/2020
Date of last issue: 04/01/2020
Date of first issue: 04/01/2020



SECTION 1. IDENTIFICATION

Product name : SOMBRA Premium Citrus Hand Sanitizer Gel
Chemical Family : Mixture

Manufacturer or supplier's details

Company name of supplier : SOMBRA Cosmetics, Inc.
Address : 5951 Office Boulevard NE
Albuquerque, NM. 87109
Telephone : 1 (505) 888-0288
Emergency telephone : 001-800-424-9300 CHEMTREC

1.1. Recommended use of the product or mixture and uses advised against

Recommended use : Hand Sanitizer to help reduce bacteria on the skin that could cause disease
Application Method : Place enough product in your palm to thoroughly cover your hands, rub together briskly until dry.
Uses advised against : Not for internal use, should not be inserted into any opening of the body

SECTION 2. HAZARD IDENTIFICATION

GHS Classification

Flammable liquids : Category 3
Eye irritation : Category 2A

GHS Label elements

Hazard pictograms : The image shows two GHS hazard pictograms side-by-side. The first is a red diamond with a black exclamation mark inside, representing a general hazard. The second is a red diamond with a black flame inside, representing a flammable hazard.

Signal Word : Warning
Hazard Statements : H226 Flammable liquid and vapor.
H319 Causes serious eye irritation.

Precautionary Statements : **Prevention:**
P101 - If medical advice is needed, have product container or label at hand.
P102 - Keep out of reach of children.

SAFETY DATA SHEET

Version:1.1
Revision Date: 7/30/2020
Date of last issue: 04/01/2020
Date of first issue: 04/01/2020



P103 - Read label before use.
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking
P233 Keep container tightly closed.
P243 Take precautionary measures against static discharge.
P264 Wash skin thoroughly after handling

[Response]:

P303+361+353 IF ON SKIN (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower.
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P337 + P313 - If eye irritation persists: Get medical advice/attention.
P370+378 In case of fire: Use extinguishing media listed in section 5 of SDS for extinction.

[Storage]:

P403+233 Store in a well-ventilated place. Keep container tightly closed.

[Disposal]:

P501 Dispose of contents / container in accordance with local / national regulations.

Other hazards

Vapors may form explosive mixture with air.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Ingredients

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Ethanol CAS Number: 64-17-5	50 - 75	Flammable Liquid 2:H225*	[1][2]
Isopropyl Alcohol CAS Number: 67-63-0	1.0 – 10.0	Flammable Liquid 2 :H225* Eye Irritant 2 ; H319 STOT SE 3; H336	[1][2]

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

*The full texts of the phrases are shown in Section 16.

SAFETY DATA SHEET

Version: 1.1
Revision Date: 7/30/2020
Date of last issue: 04/01/2020
Date of first issue: 04/01/2020



SECTION 4. FIRST AID MEASURES

4.1. Description of first aid measures

General	In all cases of doubt, or if you feel unwell, seek medical attention. Never give anything by mouth to an unconscious person
Inhalation	If breathing is difficult move to fresh air. Get medical attention if symptoms occur.
Eyes	Flush with water.
Skin	Flush with water.
Ingestion	Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If potentially dangerous quantities of this material have been swallowed, call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Overview	<p>Health Hazards (Acute and Chronic): Used as a hand sanitizer. Vapor irritates eyes. High concentration of vapor can irritate respiratory tract, are anesthetic and may cause CNS depression. Signs and Symptoms of Exposure: Confusion, headache, dizziness, and nausea.</p> <p>Medical Conditions Generally Aggravated by Exposure: Preexisting eye and respiratory disorders may be aggravated by exposure.</p> <p>Exposure to solvent vapor concentrations from the component solvents more than the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness</p> <p>Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation, and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.</p>
-----------------	--

SAFETY DATA SHEET

Version: 1.1
Revision Date: 7/30/2020
Date of last issue: 04/01/2020
Date of first issue: 04/01/2020



SECTION 5. FIRE FIGHTING MEASURES

- Suitable Extinguishing media** : Water spray
Alcohol-resistant foam
Dry chemical
Carbon dioxide (CO₂)
- Unsuitable extinguishing media** : High volume water jet.
- Specific hazards during fire fighting** : Do not use a solid water stream as it may scatter and spread fire.
Flash back possible over considerable distance.
Vapors may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.
- Hazardous combustion products** : Carbon oxides
- Specific extinguishing methods** : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.
- Special protective equipment for fire-fighters** : In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions** : Remove all sources of ignition.
- Protective equipment and emergency procedures** : Use personal protective equipment.
Follow safe handling advice and personal protective equipment recommendations.
- Environmental precautions** : Discharge into the environment must be avoided.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g. by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up** : Non-sparking tools should be used.
Soak up with inert absorbent material.
Suppress (knock down) gases/vapors/mists with a water spray jet.

SAFETY DATA SHEET

Version: 1.1
Revision Date: 7/30/2020
Date of last issue: 04/01/2020
Date of first issue: 04/01/2020



For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling : Keep away from heat, sparks, and open flames. Store at normal room temperature away from reach of small children.

Keep container closed. Avoid freezing conditions.

See section 2 for further details. - [Prevention]:

Conditions for safe storage, including any incompatibilities : Keep in properly labeled containers.
Keep containers closed.
Handle containers carefully to prevent damage and spillage.

Naked flames and smoking should not be permitted in storage areas. It is recommended that forklift trucks and electrical equipment are protected to the appropriate standard.

Incompatible materials: Incompatible with strong oxidizing agents.
Store in an explosion proof environment.

See section 2 for further details. - [Storage]:

Materials to avoid : Do not store with the following product types:
Strong oxidizing agents
Organic peroxides.
Flammable solids.
Pyrophoric liquids
Pyrophoric solids
Self-heating substances and mixtures
Substances and mixtures which in contact with water emit flammable gases
Explosives
Gases

SAFETY DATA SHEET

Version: 1.1
 Revision Date: 7/30/2020
 Date of last issue: 04/01/2020
 Date of first issue: 04/01/2020



SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION				
Ingredients with workplace control parameters				
Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Ethanol	64-17-5	TWA	1,000 ppm 1,900 mg/m ³	NIOSH REL
		TWA	1,000 ppm 1,900 mg/m ³	OSHA Z-1
Isopropyl Alcohol	67-63-0	TWA	200 ppm	ACGIH
		STEL	400ppm	ACGIH
		TWA	400ppm 980 mg/m ²	NIOSH REL
		ST	500ppm 1,225 mg/m ²	NIOSH REL
		TWA	400 ppm 980 mg ²	OSHA Z-1
Respiratory: None required under normal conditions of use				
Eyes: None required under normal conditions of use				
Skin: None required under normal conditions of use.				
Engineering Controls: Provide adequate ventilation. Where reasonably practicable.				

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: Clear to misty light yellow Gel
Odor	: Ethanol Citrus note
Odor threshold	: Not measured
pH	: 5.50 – 7.50
Melting point / freezing point	: Not measured
Initial boiling point and boiling range	: Not Measured
Flash Point (°C closed cup)	: No data available
Evaporation rate (Ether = 1)	: No data availabke
Upper/lower flammability or explosive limit	: Lower Explosive Limit: Not Measured Upper Explosive Limit: Not Measured

SAFETY DATA SHEET

Version: 1.1
Revision Date: 7/30/2020
Date of last issue: 04/01/2020
Date of first issue: 04/01/2020



Specific Gravity : 0.80 – 1.00
Solubility in Water : Completely Soluble
Viscosity : 4000 – 12,000 cP
% Ethyl Alcohol (w/w) : 59.8% - 68.2%

SECTION 10. STABILITY AND REACTIVITY

Reactivity

Hazardous Polymerization will not occur.

Chemical stability

Stable under normal circumstances.

Conditions to avoid

High temperatures and fires.

Incompatible materials

Incompatible with strong oxidizing agents

Hazardous decomposition products

High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Exposure to solvent vapor concentrations from the component solvents more than the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver, and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation, and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr	Inhalation Dust/Mist LD50, mg/L/4hr	Inhalation Gas LD50, ppm
------------	------------------	------------------	---------------------------------	-------------------------------------	--------------------------

SAFETY DATA SHEET

Version: 1.1
Revision Date: 7/30/2020
Date of last issue: 04/01/2020
Date of first issue: 04/01/2020



Ethanol - (64-17-5)	7,060.00, Rat - Category: NA	20,000.00, Rabbit - Category: NA	124.70, Rat - Category: NA	No data available	No data available
Isopropyl Alcohol - (67-63-0)	4,710.00, Rat - Category: 5	12,800.00, Rat - Category: NA	72.60, Rat - Category: NA	No data available	No data available

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Classification	Category	Hazard Description
Acute toxicity (oral)	---	Not Applicable
Acute toxicity (dermal)	---	Not Applicable
Acute toxicity (inhalation)	---	Not Applicable
Skin corrosion/irritation	---	Not Applicable
Serious eye damage/irritation	---	Not Applicable
Respiratory sensitization	---	Not Applicable
Skin sensitization	---	Not Applicable
Germ cell mutagenicity	---	Not Applicable
Carcinogenicity	---	Not Applicable
Reproductive toxicity	---	Not Applicable
STOT-single exposure	---	Not Applicable
STOT-repeated exposure	---	Not Applicable
Aspiration hazard	---	Not Applicable

SECTION 12. ECOLOGICAL INFORMATION

This product is safe for the environment at the concentration predicted under normal use conditions.

SECTION 13. DISPOSAL CONSIDERATION

Waste treatment methods

Destroy by liquid incineration. Use absorbent material and deposit in toxic landfill in accordance with local, state, and federal regulations.

SAFETY DATA SHEET

Version: 1.1
Revision Date: 7/30/2020
Date of last issue: 04/01/2020
Date of first issue: 04/01/2020



SECTION 14. TRANSPORT INFORMATION

US DOT:

Proper Shipping Name: Flammable liquids,
n.o.s., (denatured alcohol)
Hazard Class: 3
UN Number: UN1170
Packing Group: III
Labels : Limited Quantity – Flammable Liquid



DOT Hazardous Substances RQ : None/no reportable quantities
DOT Marine Pollutants: None/no reportable quantities

IATA

Proper Shipping Name: Flammable liquids, n.o.s., (denatured alcohol)
Hazard Class: 3
UN Number: UN1170
Packing Group: III
Label Statement: Limited Quantity - Flammable Liquid



INTERNATIONAL MARITIME ORGANIZATION (IMO)

Proper Shipping Name: Flammable liquids
Hazard Class: 3
UN Number: UN1170
Packing Group: III
Labels Statement : Limited Quantity - Flammable Liquid



Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

UN/ID/NA number: UN1170
Proper shipping name: ALCOHOLS, N.O.S.
Class: 3
Packing group: III
Labels: FLAMMABLE LIQUID
ERG Code: 127

SAFETY DATA SHEET

Version: 1.1
Revision Date: 7/30/2020
Date of last issue: 04/01/2020
Date of first issue: 04/01/2020



SECTION 15. REGULATORY INFORMATION

Regulatory Overview	The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.
Toxic Substance Control Act (TSCA)	All components of this material are either listed or exempt from listing on the TSCA Inventory.
WHMIS Classification	B2
US EPA Tier II Hazards	Fire: Yes Sudden Release of Pressure: No Reactive: No Immediate (Acute): No Delayed (Chronic): No
EPCRA 311/312 Chemicals and RQs:	No chemicals at levels which require reporting under this statute.
EPCRA 302 Extremely Hazardous :	No chemicals at levels which require reporting under this statute.
EPCRA 313 Toxic Chemicals:	Isopropyl Alcohol
Proposition 65 - Carcinogens (>0.0%):	No chemicals at levels which require reporting under this statute.
Proposition 65 - Female Repro Toxins (>0.0%):	No chemicals at levels which require reporting under this statute.
Proposition 65 - Male Repro Toxins (>0.0%):	No chemicals at levels which require reporting under this statute
N.J. RTK Substances (>1%):	Ethanol Isopropyl Alcohol Water
Penn RTK Substances (>1%):	Ethanol Isopropyl Alcohol Water

SAFETY DATA SHEET

Version: 1.1
 Revision Date: 7/30/2020
 Date of last issue: 04/01/2020
 Date of first issue: 04/01/2020



SECTION 16. OTHER INFORMATION	
Full text of other abbreviations	
ACGIH:	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI:	ACGIH -Biological Exposure Indices (BEI)
NIOSH REL:	USA. NIOSH Recommended Exposure Limits
OSHA Z-1:	USA. Occupational Exposure Limits (OSHA) -Table Z-1 Limits for Air Contaminants
ACGIH / TWA:	8-hour, time-weighted average
ACGIH / STEL:	Short-term exposure limit
NIOSH REL / TWA	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	STEL -15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA Z-1 / TWA	8-hour time weighted average
Sources of key data used to compile the Material Safety Data Sheet	Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, http://echa.europa.eu/
<p>The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.</p> <p>The full text of the phrases appearing in section 3 is: H225 Highly flammable liquid and vapor.</p> <p>H319 Causes serious eye irritation. H336 May cause drowsiness and dizziness. This is the first version in the GHS SDS format. Listings of changes from previous versions in other formats are not applicable.</p> <p>Disclaimer: The contents of this MSDS are believed to be correct but do not purport to be all-inclusive and should only be used as a guide. Sombra Cosmetics, Inc. disclaims any express or implied warranty as to the accuracy of the above information and shall not be held liable for any direct, incidental or consequential damages resulting from the reliance on the above information.</p>	